

## PA 1500 – Turnable roller conveyor – Type VR



### Area of application:

Roller conveyor designed to be placed on a turning module PA 1500 type VM.

### Technical data:

|                    |                                                                                                                   |
|--------------------|-------------------------------------------------------------------------------------------------------------------|
| Conveyor type:     | Fixed driven roller conveyor.                                                                                     |
| Framework:         | C-profile steel 18x70x170x70x18x4.                                                                                |
| Roller length:     | 900 and 1100mm.                                                                                                   |
| Roller spacing:    | 150mm.                                                                                                            |
| Roller type:       | Ø80x2.                                                                                                            |
| Diameter:          | 1767mm with roller 900mm.<br>1865mm with roller 1100mm.                                                           |
| Drive unit:        | Side-mounted worm gear motor.                                                                                     |
| Voltage:           | 230/400 V <sub>AC</sub> , 50Hz.                                                                                   |
| Enclosure class:   | IP55.                                                                                                             |
| Transport speeds:  | 6, 8, 10, 12, 14 and 16 m/min.                                                                                    |
| Transport heights: | See data sheet for turning module PA 1500 type VM.                                                                |
| Other:             | Protection ring is available as an accessory. It is recommended if the turnable roller conveyor is not protected. |

Observe! The protection ring is not intended to serve as collision protection from forklifts or similar. The protection ring is only there to protect people against crushing risks.